

RMF - BG3 Steel Encapsulated Panel

BSEN12825:2001 - 3/A/3/2 - RMF Medium Duty

The panel consists of a high grade 30mm high density particle board core with full FSC accreditation with a steel top lid and bottom tray all pressed together to make a fully steel encapsulated panel. Extremely dimensionally accurate it is designed to be loose laid with complete electrical continuity and has a high resistance to damage.

Product	Classification	Ultimate Load	Panel Thickness (Nominal)	System Weight (Typical)
RMF - BG3	Medium 3/A/3/2	3x > 8.0kN	31mm	33kg/m ²

Certification


The panel is fully tested to the BSEN12825:2001 3/A/3/2 specification and is fully compliant. The RMF Medium Duty BG3 panels have a 3 times working load safety factor, Class "O" spread of flame resistance and a 25 year

warranty.

Full FSC accreditation No FSC-ACC-008 TT-COC-003493.



Galvanised Steel Top Lid and Bottom Tray



Wrap Around Tray Forming Encapsulation

Finish

All of the RMF Steel Encapsulated panels are designed to be overlaid with finishes by others such as loose laid carpet tiles. Whatever your requirements, RMF will have the flooring solution to suit you.

Manufacture

All panels are manufactured for RMF in the UK, which allows us to offer total flexibility whilst maintaining the highest possible quality standard and ensures fast reaction and a reliable service. Materials used are sourced from high quality suppliers and use renewable, sustainable sources and suppliers wherever possible. We can also offer a bespoke service and specialise in replicating and reproducing existing raised floors.



RMF Installation & Services Ltd

For more information call:

01926 425289

sales@rmf-services.co.uk