

# RMF – BGM600 Steel Encapsulated Panel

PSA MOB PF2 PS/SPU Medium Grade


The panel consists of a high grade 30mm high density particle board core with full FSC accreditation with a steel top lid and bottom tray all pressed together to make a fully steel encapsulated panel. Extremely dimensionally accurate it is designed to be loose laid with complete electrical continuity and has a high resistance to damage.

Product	Panel Grade	25mm Point Load	Load over 300mm	Uniform Distributed	Panel Thickness (Nominal)	System Weight (Typical)
RMF – BGM	Medium	3.0kN	4.5kN	8.0kN	31mm	33kg/m <sup>2</sup>

## Certification

The RMF BGM600 panel is fully tested by an independent UKAS accredited laboratory to the PSA MOB PF2 PS/SPU March 19925 Medium Grade specification and is certified as being fully compliant. All of the RMF PSA panels have a 3 times working load safety factor, Class "0" spread of flame resistance and a 25 year warranty.

Full FSC accreditation No FSC-ACC-008 TT-COC-003493.



Wrap Around Tray Forming Encapsulation

Galvanised Steel Top Lid and Bottom Tray



## Finish

All of the RMF Steel Encapsulated panels are designed to be overlaid with finishes by others such as loose laid carpet tiles. Whatever your requirements, RMF will have the flooring solution to suit you.

## Manufacture

All panels are manufactured for RMF in the UK, which allows us to offer total flexibility whilst maintaining the highest possible quality standard and ensures fast reaction and a reliable service. Materials used are sourced from high quality suppliers and use renewable, sustainable sources and suppliers wherever possible. We can also offer a bespoke service and specialise in replicating and reproducing existing raised floors.



RMF Installation & Services Ltd

For more information call:

01926 425289

[sales@rmf-services.co.uk](mailto:sales@rmf-services.co.uk)

Hangar One, Harbury Lane, Leamington Spa, CV33 9SA